



TEST REPORT

Applicant : SPECTOR & CO
Address : 5700 KIERAN ROAD, ST. LAURENT, QUEBEC, Canada H4S 2B5
Report No : 140923040SZN-002 **Issue Date** : Nov. 28, 2014

Sample Description

Type of Product : Bluetooth speaker
Brand : /
Model No. of Product : T270
Date of Received : Sep. 24, 2014
Date of test Conducted : Nov. 3, 2014 – Nov. 7, 2014

Test

Test Method : UL/CSA 60065 Clause 14.10.4, Clause 14.10.5, Clause 11.2
Sample quantity : 2
Test Observation: : See pages 2-5 for details.
Remark : When determine the test result, measurement uncertainty has been considered.

***** End of page *****

Tested By

Approved by:

Signed on file

Simon Sun
Project Engineer

Wisons Lin
Project Engineer

Note: This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. The test report only allows to be revised only within the report defined retention period unless standard or regulation was withdrawn or invalid.

Clause	Requirement + Test	Result - Remark	Verdict
11	Fault conditions		P
11.1	No shock hazard under fault condition		P
11.2	Heating under fault condition		P
	Flames extinguish within 10 seconds	No flame during testing	N/A
	No hazard from softening solder	No softening solder	N/A
	Soldered terminations not used as protective mechanism		P
11.2.1	Measurement of temperature rises	(see appended table 11.2)	P
11.2.2	Temperature rise of accessible parts	(see appended table 11.2)	P
11.2.3	Temperature rise of parts, other than windings and printed boards, providing electrical insulation	No such parts	N/A
11.2.4	Temperature rise of parts acting as a support or mechanical barrier	No such parts	N/A
11.2.5	Temperature rise of windings	(see appended table 11.2)	P
11.2.6	Temperature rise of printed boards shall not exceed the limits of table 3 by max. 100 K for max. 5 min	(see appended table 11.2)	P
	Printed circuit boards (PCB) classified as V-0 according to 60695-11-10 or Clause G.1 may exceed the limit in table 3 in case a) and b):		N/A
	a) Temperature rise of printed circuit boards exceeding the limits of table 3 by not more than 100 K for an area not greater than 2 cm ²		N/A
	b) Temperature rise of printed circuit boards exceeding the limits of table 3 up to 300 K for an area not greater than 2 cm ² for a maximum of 5 min		N/A
	Meets all the special conditions if conductors on printed circuit boards are interrupted		N/A
	Class I protective earthing maintained		N/A
11.2.7	Temperature rise of parts not subject to the limits of 11.2.1 to 11.2.6 shall not exceed the limits in table 3, item e), "Fault conditions".		N/A
14	Components		P
14.10.4	Battery mould stress relief		P
14.10.5	Battery drop test		P

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

11.2	TABLE: summary of fault condition tests			P
	Voltage (V) 0,9 or 1,1 times rated voltage	5V DC		—
	Frequency (Hz)	/		—
	Ambient temperature (°C)	24 °C – 35 °C		—
No.	Component	Fault	dT (K) / Component	Other results (include description and test duration)
1.	Battery output	SC	/	The apparatus was protected immediately and the input current dropped to 0A, no hazardous phenomena
2.	Speaker	SC	20/PCB surface(near SS14) 14/PCB surface(near IC1) 14/PCB surface(near IC2) 14/PCB surface(near IC3) 20/PCB surface(near IC4) 15/PCB surface(near IC5) 12/Battery surface 10/Internal enclosure surface(non-metallic) 9/External enclosure surface(non-metallic)	Un(V) = 5,5; Pn(W) = 3,98; In(mA) = 723 Result: No hazards.
3.	Battery	Overcharge	19/PCB surface(near SS14) 12/PCB surface(near IC1) 13/PCB surface(near IC2) 12/PCB surface(near IC3) 12/PCB surface(near IC4) 12/PCB surface(near IC5) 11/Battery surface 9/Internal enclosure surface(non-metallic) 9/External enclosure surface(non-metallic)	Un(V) = 5,5; Pn(W) = 2,66; In(mA) = 483 Result: No hazards. No temperature rise exceeding its limit occurred.

Note:

1. Max=max non-clipped or available output power, SC=short circuit, OL=over load, BL=block.

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

Photo:

