



TEST REPORT

Applicant : SPECTOR & CO
Address : 5700 KIERAN ROAD, ST. LAURENT, QUEBEC, Canada H4S 2B5
Supplier : XINVO **Vendor Code** : USX007
Report No : 140923040SZN-003 **Issue Date** : Dec. 18, 2014

Sample Description

Type of Product : Bluetooth speaker
Brand : /
Model No. of Product : T270
Date of Received : Sep. 24, 2014
Date of test Conducted : Dec. 8, 2014 – Dec 17, 2014

Test

Test Method : UN38.3 Test T.7
Sample quantity : 1
Test Observation: : See pages 2-4 for details.
Remark : When determine the test result, measurement uncertainty has been considered.

***** End of page *****

Tested By

Approved by:

Signed on file

Simon Sun
Project Engineer

Jack Yang
Supervisor

Note: This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. The test report only allows to be revised only within the report defined retention period unless standard or regulation was withdrawn or invalid.

Battery information	
Battery category	Lithium Ion
Manufacturer	Not provided
Type / model.....	053040S
Voltage	3.7V
Capacity.....	400mAh
Tested and Certified by (incl. Ref. No.).	/
Circuit protection diagram:	Not provided

38.3.4.7 Test T.7: Overcharge

38.3.4.7.1 Purpose

This test evaluates the ability of a rechargeable battery to withstand an overcharge condition.

38.3.4.7.2 Test procedure

The charge current shall be twice the manufacturer's recommended maximum continuous charge current. The minimum voltage of the test shall be as follows:

(a) when the manufacturer's recommended charge voltage is not more than 18V, the minimum voltage of the test shall be the lesser of two times the maximum charge voltage of the battery or 22V.

(b) when the manufacturer's recommended charge voltage is more than 18V, the minimum voltage of the test shall be 1.2 times the maximum charge voltage.

Tests are to be conducted at ambient temperature. The duration of the test shall be 24 hours.

38.3.4.7.3 Requirement

Rechargeable batteries meet this requirement if there is no disassembly and no fire during the test and within seven days after the test.


Result:

The battery is disassembly and no fire during the test and within seven days after the test.

Photo:



Product



Battery